



# XHF™ Spray Gun

High-Flow, High-Pressure Gun



## Designed for the most demanding materials

- Handles high viscosity protective coatings
- Designed for reduced plugging with epoxy intumescent coatings and fiber-filled materials
- Rugged and durable for less downtime

PROVEN QUALITY. LEADING TECHNOLOGY.



# Rugged and Capable

## Technical Specifications

Maximum working pressure	7250 psi (500 bar, 50 MPa)
Fluid orifice size	0.125 in (3.2 mm)
Inlet size	3/8 npt(m)
Weight (includes tip and tip guard)	1.45 lb (658 g)
Wetted parts	Tungsten carbide, 17-4PH passivated stainless steel, polypropylene, polyethylene
Manual	3A2799A

## Ordering Information

### XHF Gun

262854 XHF Gun, includes XHD 429 tip

### Accessories

237260 XHF Gun repair kit

24P834 XHF Gun swivel, 1/2 in f x 3/8 npsm, PTFE packing, 6500 psi (448 bar, 44.8 MPa)

246294 10 in (254 mm) gun extension, 7250 psi (500 bar, 50 MPa)

246295 15 in (380 mm) gun extension, 7250 psi (500 bar, 50 MPa)

246296 18 in (457 mm) gun extension, 7250 psi (500 bar, 50 MPa)

246297 180° spray nozzle, 7/8 UNC-2B, 7250 psi (500 bar, 50 MPa)

XHD\_\_\_ Heavy duty RAC® SwitchTip  
(Last three digits correspond to tip size)

XHD001 XHD RAC housing, aluminum, hand tight - included with gun

XHD003 XHD RAC housing, SST, wrench tight - for extended thread life

### Heavy fluid needle

- Maximize uptime
- No spring in fluid path



### Front-entry fluid housing

- High pressure, up to 7250 psi (500 bar, 50 MPa)
- High flow and high production
- Ideal for fibrous or heavily filled materials

### Four-finger trigger with safety lock

- Contoured for comfort

### Ergonomic gun body

- Light weight forged aluminum
- Form fitted handle for less fatigue



### Rugged, Reliable and Easy to Maintain

#### XHD™ RAC® SwitchTip™ and Housing

- Handles high solids coatings
- Hand-tight installation
- Tool-less tip removal

## Contact us today!

For more information, call **1-877-844-7226**

or visit **www.graco.com**